[redacted]

Fax

RECEIVED
CENTRAL FAX CENTER
SEP 19 2005

To: Mr. Yean Hsi Chang **From:** Eric Wells

Fax: (571) 273-8300 **Pages:** 32 Pages(Including Cover Letter)

Phone: (662) 838-4579 **Date:** September 19, 2005

Re: Patent **CC:**

☐ **Urgent** ☒ **For Review** ☐ **Please Comment** ☐ **Please Reply** ☐ **Please Recycle**

PTO/SB/21 (09-04)
Approved for use through 07/31/2006. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

TRANSMITTAL FORM

(to be used for all correspondence after initial filing)

Total Number of Pages in This Submission: 19

Application Number	10/603246
Filing Date	6-26-03
First Named Inventor	Eric Wells
Art Unit	2835
Examiner Name	Yean-Hsi Chang
Attorney Docket Number	

ENCLOSURES (Check all that apply)

- ☐ Fee Transmittal Form
  - ☐ Fee Attached
- ☐ Amendment/Reply
  - ☐ After Final
  - ☐ Affidavits/declaration(s)
- ☐ Extension of Time Request
- ☐ Express Abandonment Request
- ☐ Information Disclosure Statement
- ☐ Certified Copy of Priority Document(s)
- ☐ Reply to Missing Parts/ Incomplete Application
  - ☐ Reply to Missing Parts under 37 CFR 1.52 or 1.53
- ☒ Drawing(s)
- ☐ Licensing-related Papers
- ☐ Petition
- ☐ Petition to Convert to a Provisional Application
- ☐ Power of Attorney, Revocation Change of Correspondence Address
- ☐ Terminal Disclaimer
- ☐ Request for Refund
- ☐ CD, Number of CD(s) _____
  - ☐ Landscape Table on CD
- ☐ After Allowance Communication to TC
- ☐ Appeal Communication to Board of Appeals and Interferences
- ☐ Appeal Communication to TC (Appeal Notice, Brief, Reply Brief)
- ☐ Proprietary Information
- ☐ Status Letter
- ☐ Other Enclosure(s) (please identify below):

Remarks

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT

Firm Name			
Signature	Eric Wells		
Printed name	Eric Wells		
Date	8-25-05	Reg. No.	

CERTIFICATE OF TRANSMISSION/MAILING

I hereby certify that this correspondence is being facsimile transmitted to the USPTO or deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date shown below:

Signature	Eric Wells		
Typed or printed name	Eric Wells	Date	8-25-05

611 Jennette Place
Memphis, TN 38126
September 19, 2005

Mr. Yean-Hsi Chang
Art Unit 2835
Commissioner for Patents
P. O. Box 1450
Alexandria, VA 22313-1450

Re: Wrong Telephone Number Received to send Facsimile

Dear Mr. Chang:

This letter is in reference to our conservation, held on Wednesday, September 14, 2005 about you not receiving the patent. I am resubmitting a copy of the information I sent to you with the correct fax number you gave me.

Sincerely yours,

Eric Wells

Mr. Yean-His Chang
Art Unit 2835
Commissioner for Patents
P. O. Box 1450
Alexandria, VA 22313-1450

Dear Mr. Chang:

This is verification that the patent facsimile was sent to you on August 25, 2005.

Yours truly,

Eric Wells

Eric Wells

PAGE 5/47 * RCVD AT 9/19/2005 8:52:49 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/28 * DNIS:2738300 * CSID:6628384579 * DURATION (mm-ss):14-40

THIS PAGE BLANK (USPTO)

PAGE 6/47 * RCVD AT 9/19/2005 8:52:49 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/28 * DNIS:2738300 * CSID:6628384579 * DURATION (mm-ss):14-40

THIS PAGE BLANK (USPTO)

FROM: Name:
Voice Phone:

PAGE 7/47 * RCVD AT 9/19/2005 8:52:49 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/28 * DNIS:2738300 * CSID:6628384579 * DURATION (mm-ss):14-40

THIS PAGE BLANK (USPTO)

Please lower your [illegible]
what department you are sending this to.

PAGE 8/47 * RCVD AT 9/19/2005 8:52:49 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/28 * DNIS:2738300 * CSID:6628384579 * DURATION (mm-ss):14-40

THIS PAGE BLANK (USPTO)

Date and time of transmission: Friday, August 26, 2005 8:03:04 AM
PAGE 9/47 * RCVD AT 9/19/2005 8:52:49 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/28 * DNIS:2738300 * CSID:6628384579 * DURATION (mm-ss):14-40

THIS PAGE BLANK (USPTO)

PAGE 10/47 * RCVD AT 9/19/2005 8:52:49 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/28 * DNIS:2738300 * CSID:6628384579 * DURATION (mm-ss):14-40

PAGE 11/47 * RCVD AT 9/19/2005 8:52:49 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/28 * DNIS:2738300 * CSID:6628384579 * DURATION (mm-ss):14-40

THIS PAGE BLANK (USPTO)

THIS PAGE BLANK (USPTO)

PAGE 13/47 * RCVD AT 9/19/2005 8:52:49 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/28 * DNIS:2738300 * CSID:6628384579 * DURATION (mm-ss):14-40

THIS PAGE BLANK (USPTO)

THIS PAGE BLANK (USPTO)

FROM : EVT PHONE NO. : 6628384579 Aug. 25 2005 05:43PM P01

PAGE 15/47 * RCVD AT 9/19/2005 8:52:49 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/28 * DNIS:2738300 * CSID:6628384579 * DURATION (mm-ss):14-40

THIS PAGE BLANK (USPTO)

	10/603246
Filing Date	/ 07 03

THIS PAGE BLANK (USPTO)

Appeal Final | Provisional Application | Proprietary Information
Power of Attorney, Revocation | Status Letter

PAGE 17/47 * RCVD AT 9/19/2005 8:52:49 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/28 * DNIS:2738300 * CSID:6628384579 * DURATION (mm-ss):14-40

THIS PAGE BLANK (USPTO)

PAGE 6/22 * RCVD AT 9/19/2005 6:41:45 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/26 * DNIS:4612898 * CSID:6628384579 * DURATION (mm-ss):04-20
PAGE 18/47 * RCVD AT 9/19/2005 8:52:49 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/28 * DNIS:2738300 * CSID:6628384579 * DURATION (mm-ss):14-40

THIS PAGE BLANK (USPTO)

THIS PAGE BLANK (USPTO)

XMT REPORT

Aug. 25 2005 05:47PM

NO.	OTHER FACSIMILE	START TIME	USAGE TIME	MODE	PAGES	RESULT	CODE
01		Aug. 25 5:41PM	04'06	TX	22	DOCUMENT JAMMED	(A3)

Reference Numerals in Drawings

1	Handle
2	Mice
3	Speakers
4	Right Keyboard
5	Left Keyboard
6	Knockout Panels
7	Right Display Screen
8	Left Light Indicators
9	Left Display Screen
10	Right Light Indicator
11	Plug-In Play Slots (right)
12	Plug-In Play Slots (left)
13	Plug-In Play Slots (left, right, & rear)
14	Plug-In Play Slots (rear)
15	Mounting Board
16	Lifting Lid
17	Top Lid (side view)
18	Back Housing to Display Screen
19	Metal Frame
20	Mounting Plate & Screws for Rubber Restrainer
21	Front Cover for Rubber Display
22	Perforated Section for Front Rubber Cover Display
23	Holding Screws
24	Bracket Mount
25	Vertical Arm for Mount
26	Holding Screws
27	Horizontal Tract
28	Bracket Mount
29	Holding Screw
30	Area to Housing Display Screen
31	Sliding Mounting Unit (Rear Cover)
32	Perforated Section for Sliding Mounting Unit
33	Outer Facing Cover for Sliding Mounting Unit
34	Outside Housing for the Bubbled Edge of Rear Display Unit
35	Solar Panel (Center of & Rear View)
36	Inner Bubbled Edge
37	Lighting Indicators
38	Power Light Indicator
39	Right Side of Display Screen
40	Left Side of Display Screen
41	Retractable Feet
42	Hinges
43	Mounted Motherboards
44	MCICIA Card Slot
45	Left Expansion Drawer
46	Right Expansion Drawer
47	Retracting Handle (Side View)
48	Retracting Handle (Top View)

49	Retracting Handle (Alternate View)
50	Access Flap
51	Ventilation Holes
52	Bottom Mounting Screws
53	Back View of Middle Section
54	Antenna
55	Plug-In Connection & Flap
56	Ventilation Fan
57	Back Section of Case
58	Mounting Board
59	Mounting Screw
60	Mounting Holes on Board
61	Close-up View of Mounting Holes on Board
62	Close-up View of Mounting Holes
63	Locking Apparatus for Expandable Drawer
64	Plug-in Play Slots
65	System Data and Power Flow Network Locations
66	System Network Diagram
67	Slide-Out Panel
68	Slide-Out Bay with Panel
69	Slide-Out Side Drawers
70	Temperature Controls
71	Temperature Cooling Assembly
72	Temperature for Middle and Bottom Case
73	Temperature Control System
74	Power Supply
75	Display Controllers
76	Internal Network
77	Switching Network
78	Auxiliary Keyboards
79	Detachable Firmware
80	Interface with Stylus Pen
81	Keyboard and Third Mouse
82	Hinges on Case Sections
83	Hinges and Power connections for Solar Cells

Reference Numerals in Drawings

1	Handle
2	Mice
3	Speakers
4	Right Keyboard
5	Left Keyboard
6	Knockout Panels
7	Right Display Screen
8	Left Light Indicators
9	Left Display Screen
10	Right Light Indicator
11	Plug-In Play Slots (right)
12	Plug-In Play Slots (left)
13	Plug-In Play Slots (left, right, & rear)
14	Plug-In Play Slots (rear)
15	Mounting Board
16	Lifting Lid
17	Top Lid (side view)
18	Back Housing to Display Screen
19	Metal Frame
20	Mounting Plate & Screws for Rubber Restrainer
21	Front Cover for Rubber Display
22	Perforated Section for Front Rubber Cover Display
23	Holding Screws
24	Bracket Mount
25	Vertical Arm for Mount
26	Holding Screws
27	Horizontal Tract
28	Bracket Mount
29	Holding Screw
30	Area to Housing Display Screen
31	Sliding Mounting Unit (Rear Cover)
32	Perforated Section for Sliding Mounting Unit
33	Outer Facing Cover for Sliding Mounting Unit
34	Outside Housing for the Bubbled Edge of Rear Display Unit
35	Solar Panel (Center of & Rear View)
36	Inner Bubbled Edge
37	Lighting Indicators
38	Power Light Indicator
39	Right Side of Display Screen
40	Left Side of Display Screen
41	Retractable Feet
42	Hinges
43	Mounted Motherboards
44	MCICIA Card Slot
45	Left Expansion Drawer
46	Right Expansion Drawer
47	Retracting Handle (Side View)
48	Retracting Handle (Top View)

26, & 29) to hold the display screen in place. There are also vertical pieces (25) that are held in place by brackets (22 & 28). There is a face cover (33) with knockout sections (32) to house the display screen (30).

The middle section has a handle (1) that retracts into the case. Illustrations 47, 48, & 49 are different views of the handle. There is a space to the left and right of the handle, which has knockout panels (6). The top is the area in which most of the input devices are mounted. The top can be lifted up to have access to the inside (16). Underneath the top, at the bottom of the case, one or more boards can be mounted (43). Also, there is an area where one or more daughterboards or one or more expansion slots (11, 12, 13, & 14) can be placed. The case, from the bottom, has two mice (2) to use in controlling the display unit. Also, there are two speakers (3) at the bottom, connected to the bottom lid.

The next section is the keyboard (4 & 5). The keyboard (4) on the right of the console will be stationary. The keyboard on the left (5) will be removable and will work by Radio Frequency. The left keyboard will have a built-in mouse or tracker ball. The next part on the console will be the Liquid Crystal Display (7 & 9) with indicator lights (8 & 10). The inside of the middle section is where the motherboards for the units will be housed and the Micro Computer Integrated Card Industry Association (44) will be placed. This unit will house circuit boards, some small batteries, and plug-in-place slots inside (11, 12, 13, & 14). There is a single profile indicating how the speakers and mice will set on the top panel (17). There is one other section that is ventilated, the middle (53) section. This section will have a small fan to pull heat from the electronic boards and small ventilation holes in front so air can circulate. In the back where this ventilation fan is located (56), there will be an opening entrance with a door that closes to hide the plug-in connections (55). One other part, which is the antenna (54) is connected on the back. Illustration (57) is a streamline section of the rear of the case where it fits together.

There is a locking apparatus to set the distance on the end pieces (63). These end pieces can only be pulled out to a certain point and then will lock in place.

In order to hold everything in place, screws can be placed from the bottom (48). These screws will hold mostly the mounting board (15), but can hold other components directly. The board that sets in the bottom has holes that have grooves. A notch screw fits into the holes and twists to lock them. These are shown in (60, 61, & 62). Figures (58 & 59) will give you a better concept of the mounting board and screw.

The entire network is composed of several key areas that is given in a generalized flow chart of the system's network. This will explain the use with this and other flow charts of the component placement and configuration within the case (65).

The peripheral holes are covered with slide-out panels (66). The slide-out panels are for the covers that are removable from the bay fittings (67). The bay that houses the slide-out panels also slide out for sizing large components, with rubber, to give close fitting around components. The expandable, hybridized case, which means two or more different types of components coming together as one, accepts placement and spacing of traditional computer parts, laptop parts, and digital controller boards, that fit in the case with expandable, sliding drawers, for larger and different component housing (68). There is, also, a liquid cooling system with a miniature fluid pump rotating through capillaries to fins in heat sinks in top and bottom sections of the case (69). This section has temperature control monitoring to cool the inside of the case in sections, which is achieved in sections by a plastic film that is either horizontal or vertical, to separate the different sections for desired temperatures in the middle and bottom casing section. One of the main sections of the casing is the power supply, which is composed of Direct Current to Alternating Current inverters and Alternating Current to Direct Current converters for different power needs, with indicators to show power display (70). Computer components operate together to vary the functions through switching of circuits, operating singularly or networking together in parallel, to control peripherals, digital circuits, and analogue circuits (71). Also, there is an interconnecting interface to allow all computers to connect to other computers in the case (72). Another section is the detachable software, which we refer to as firmware for clarity. This is removable, embedded, software, or as stated, firmware (73). This display system and its interactive presentation can be interfaced with a stylus light pen (74). Other input devices such as the two keyboards and the third mouse, which is smart enough, can allow for multi-interfacing functions (75). The top display lid has solar panels, which are angular in geometry to increase the surface area in a given space (76). Also, on the sides of the top display lid, there are simple, inner-connecting hinges that lock to additional, adjoining, solar panels (77). The mounting board, spoken of previously, is flexible enough to allow for a multi-facet of spacing and connectivity of components, which may be joined together either singularly or in a parallel union (78).